



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/775,275	02/10/2004	Laszlo Lipcsei	O2Micro 04.01	1281

32047 7590 12/29/2005

GROSSMAN, TUCKER, PERREAULT & PFLEGER, PLLC  
55 SOUTH COMMERICAL STREET  
MANCHESTER, NH 03101

EXAMINER
----------

MURALIDAR, RICHARD V

ART UNIT	PAPER NUMBER
----------	--------------

2838

DATE MAILED: 12/29/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

**Office Action Summary**

Application No.

10/775,275

Applicant(s)

LIPCSEI ET AL.

Examiner

Richard V. Muralidar

Art Unit

2838

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 02/10/2004.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-23 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-23 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☒ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 07/08/2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
- Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |   |   |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)             | 4) <input type="checkbox"/> Interview Summary (PTO-413)                     |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)    | Paper No(s)/Mail Date. _____  |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| Paper No(s)/Mail Date _____   | 6) <input type="checkbox"/> Other: _____                                    |

## **DETAILED ACTION**

### ***Specification***

The title of the invention is not descriptive. A new title is required that is clearly indicative of the invention to which the claims are directed.

The following title is suggested: Power Converter with Switches that Short the Primary and Secondary Windings of the Transformer. Appropriate correction is required.

### ***Claim Objections***

Claim 16 is objected to because it presents no new inventive information over the preceding claims 1-15.

### ***Claim Rejections - 35 USC § 102***

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) The invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 1-23 are rejected under 35 U.S.C. 102(e) as being anticipated by Wei [2004/0100805].

With respect to Claims 1 and 6, Wei discloses an electronic device [par. 0005 lines 1-5, microprocessor with a power converter] comprising: a power converter to accept an input power signal [Fig. 2 Vin] and provide an output power signal [Fig. 2 Vout], said power converter comprising: a transformer having a primary winding and a secondary winding [Fig. 2 transformer M, primary W1, secondary W2]; and a plurality

Art Unit: 2838

of switches coupled to said primary and secondary winding [Fig. 2 switches Q1-Q6], said plurality of switches responsive to at least one control signal to short both said primary and secondary winding during a first reset time interval [page 2, par. 0023; Fig. 4C shows switches Q2 and Q3 operable to short both primary and secondary of transformer M].

With respect to Claims 2 and 7, Wei discloses that said plurality of switches comprises: a first high side switch [Fig. 2 switch Q1] and a first low side switch [Fig. 2 switch Q3] coupled in series along a first path [Fig. 2 path 22] of a full bridge circuit [Fig. 2 switches Q1-Q4], a first node between said first high side switch and said first low side switch [Fig. 2 node 24]; and a second high side switch [Fig. 2 switch Q4] and a second low side switch [Fig. 2 switch Q2] coupled in series along a second path [Fig. 2 path 20] of said full bridge circuit, a second node [Fig. 2 node 24] between said second high side switch and said second low side switch, wherein said primary winding [Fig. 2 primary W1] is coupled between said first node and said second node, and wherein said first and second high side switches [Q1 and Q4] are adapted to open and said first and second low side switches [Q2 and Q3] are adapted to close during said first reset time interval to short said primary winding [Fig. 4C free wheeling mode].

With respect to Claims 3 and 8, Wei discloses that said plurality of switches further comprises: a first rectifier switch coupled to one end of said secondary winding [Fig. 2 switch Q5]; and a second rectifier switch coupled to an opposite end of said secondary winding [Fig. 2 switch Q6], wherein said first and second rectifier switches are adapted to close during said first reset time interval to short said secondary winding

[Fig. 4A and 4C free wheeling mode show the rectifier switches shorting the secondary to ground].

With respect to Claims 4 and 9, Wei discloses that said first low side switch [Q2] of said first path of said full bridge circuit and said first rectifier switch [Q5] are responsive to a first control signal and said second low side switch [Q3] of said second path of said full bridge circuit and said second rectifier switch [Q6] are responsive to a second control signal [the configurations in Fig 4C, 7A and 7C show that Q2 and Q5 are synchronized, and Q3 and Q6 are synchronized].

With respect to Claims 5 and 10, Wei discloses that said first high side switch [Q4] of said first path of said full bridge circuit is responsive to a third control signal and said second high side switch [Q1] of said second path of said full bridge circuit is responsive to a fourth control signal [Figs. 4A, 4C, 7A and 7C show switches Q4 and Q1 synchronized].

With respect to Claim 11, Wei discloses a method comprising: sampling an input voltage onto a primary winding of a transformer during a first time interval; and shorting said primary winding of said transformer during a second time interval [Fig. 4C encompasses this method].

With respect to Claim 12, Wei discloses a method shorting a secondary winding of said transformer during said second time interval [Fig. 4A encompasses this method].

With respect to Claim 13, Wei discloses a method comprising: providing a first control signal [Fig. 3 control signal Q4] to control a state of a first high side switch [Fig. 2 Q4] coupled to a first path of a full bridge circuit [Fig. 2 switches Q1-Q4]; providing a

Art Unit: 2838

second control signal [Fig. 3 control signal Q1] to control a state of a second high side switch [Fig. 2 Q1] coupled to a second path of said full bridge circuit, said full bridge circuit coupled across a primary winding of a transformer [Fig. 2 primary winding W1]; providing a third control signal to simultaneously control [Figs. 4C and 7C show Q2 and Q5 operating simultaneously] a state of a first low side switch [Fig. 2 Q2] coupled to said first path of said full bridge circuit and a state of a first rectifier switch of a rectifier circuit [Fig. 2 Q5], said first rectifier switch coupled to one end of a secondary winding of said transformer [Fig. 2 secondary winding W2]; and providing a fourth control signal to simultaneously control [Figs. 4C and 7C show Q3 and Q6 operating simultaneously] a state of a second low side switch [Fig. 2 Q3] coupled to said second path of said full bridge circuit and a state of a second rectifier switch [Fig. 2 Q6] of said rectifier circuit, said second rectifier switch coupled to an opposite end of said secondary winding of said transformer.

With respect to Claim 14, Wei discloses a method comprising: shorting said primary winding [Fig. 2 secondary W1] during a first time interval by closing said first low side switch [Fig. 2 Q2] of said first path of said full bridge circuit and by closing said second low side switch [Fig. 2 Q3] of said second path of said full bridge circuit during said first time interval [Fig. 4C and 7C show Q2 and Q3 shorting the primary of the transformer].

With respect to Claim 15, Wei discloses a method comprising: shorting said secondary winding [Fig. 2 primary W1] during said first time interval by closing said first rectifier switch [Fig. 2 Q5] and by closing said second rectifier switch [Fig. 2 Q6] during

said first time interval [Fig. 4A and 4C show Q5 and Q6 shorting the secondary of the transformer].

With respect to Claim 16, Wei discloses a power converter comprising: a full bridge circuit having a first path and a second path, each path comprising a high side and low side bridge switch connected in series, each path having a node between said high side and low side bridge switches, and each path coupled to an input voltage terminal; a transformer having a primary winding and a secondary winding, said primary winding being coupled between said nodes of said paths of said full bridge circuit; and a rectifier circuit coupled to said secondary winding, said rectifier circuit comprising a first and second rectifier switch, said first rectifier switch coupled to one end of said secondary winding, said second rectifier switch coupled to an opposite end of said secondary winding, said low side switch of said first path and said first rectifier switch simultaneously driven by a first control signal and said low side switch of said second path and said second rectifier switch simultaneously driven by a second control signal [covered in previous claims, and shown in Fig. 2, Fig. 4A, Fig 4C, page 2 par. 0023].

With respect to Claim 17, Wei discloses that high side switches [Fig. 2 Q1 and Q4] of said first and second paths are adapted to open [Fig. 4C show them opened] and said low side switches [Fig. 2 Q2 and Q3] of said first and second paths are adapted to close [Fig. 4C show them closed] during a reset time interval to short said primary winding [Fig. 4C shows primary winding W1 shorted to secondary winding W2].

With respect to Claim 18, Wei discloses that said first and second rectifier

Art Unit: 2838

switches [Fig. 2 Q5 and Q6] are also adapted to close during said first reset time interval to short said secondary winding during said reset time interval [Fig. 4C show Q5 and Q6 closed, in conjunction with Q2 and Q3 closed, and Q1 and Q4 opened].

With respect to Claim 19, Wei discloses a power converter comprising a plurality of DC to DC converters coupled in parallel [page 4 par. 0053; Fig. 8], at least one of said plurality of DC to DC converters [Fig. 8 converters 28, 30, 32, 34] comprising: a transformer [M1] having a primary winding and a secondary winding [W1 and W2]; and a plurality of switches coupled to said primary and second winding [switches Q1-Q8], said plurality of switches responsive to at least one control signal to short both said primary and secondary winding during a first reset time interval [Fig. 8 is the plural version of Fig. 2, with multiple, parallel output converters connected to the secondary, therefore the primary and secondary are shorted in the same manner].

With respect to Claim 20, Wei discloses that said plurality of switches comprises: a first high side switch and a first low side switch coupled in series along a first path of a full bridge circuit, a first node between said first high side switch and said first low side switch; and a second high side switch and a second low side switch coupled in series along a second path of said full bridge circuit, a second node between said second high side switch and said second low side switch, wherein said primary winding is coupled between said first node and said second node, and wherein said first and second high side switches are adapted to open and said first and second low side switches are adapted to close during said first reset time interval to short said primary winding [Fig. 8 is the plural version of Fig. 2, with multiple, parallel output converters



Art Unit: 2838

connected to the secondary. Therefore the first and second high side switches and first and second low side switches respectively open and close in exactly the same manner as described for Fig. 2 for the previous claims].

With respect to Claim 21, Wei discloses that said plurality of switches further comprises: a first rectifier switch coupled to one end of said secondary winding; and a second rectifier switch coupled to an opposite end of said secondary winding, wherein said first and second rectifier switches are adapted to close during said first reset time interval to short said secondary winding [Fig. 8 is the plural version of Fig. 2, with multiple, parallel output converters connected to the secondary. Therefore the first and second rectifier switches close to short the secondary winding in exactly the same manner as described for Fig. 2 for the previous claims].

With respect to Claim 22, Wei discloses that said plurality of switches for each said DC to DC converter are responsive to control signals from a driver associated with each said DC to DC converter [page 2 par. 0026].

With respect to Claim 23, Wei discloses that said plurality of switches comprise MOSFET transistors [page 2, par. 0026 states Q1-Q6 are FETs; the most popular ones are known to be MOSFETs] and said driver comprises a dual MOSFET driver [page 2, par. 0026, the driving circuit is well known in the art, and the MOSFET driver/ dual driver is widely used to drive MOSFETs].

**Conclusion**

The following reference is cited for its disclosure of a non-isolated bridge buck DC-DC converter with self-driven synchronous rectifiers. Xu [US2004/0246748A1] uses a similar arrangement of transistors to short circuit the primary and secondary windings of a transformer to ground.


Any inquiry concerning this communication or earlier communications from the examiner should be directed to Richard V. Muralidar whose telephone number is 571-272-8933. The examiner can normally be reached on Monday to Friday 8-5.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Gray can be reached on Monday to Friday 8-5. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

RVM  
12/23/2005

Richard V Muralidar  
Examiner  
Art Unit 2838

A handwritten signature in black ink, appearing to read 'David Gray', with a long horizontal line extending to the right.

David Gray  
Primary Examiner